

**SPECIFICATIONS**

- ✓ Star Delta Starter application
- ✓ Suitable for higher HP motors
- ✓ Two relay contacts for Star & Delta
- ✓ Pause time between two relay changeover
- ✓ Time range 60 Sec
- ✓ Time adjustable by Pot
- ✓ LED Indications for Star & Delta
- ✓ Auxiliary supply 230VAC / 440VAC
- ✓ Enclosure : Din Rail Mounting
- ✓ Size : 50 X 70 X 110 mm

**ET5SD**

---

---

**SPECIFICATIONS**

- ✓ ON Delay / Interval / Cyclic equal configurations possible
- ✓ Time range 15 Sec, 60 Sec, 8Min, 64 Min
- ✓ Time adjustable by Pot
- ✓ LED Indications for Power & Time
- ✓ One relay output contact rating 5A t 230V
- ✓ Auxiliary supply 230VAC / 440VAC
- ✓ Enclosure : Din Rail Mounting
- ✓ Size : 50 X 70 X 110

**ET1**

---

---

---

---

## SPECIFICATIONS

- ✓ Used for Electrical Soft Starter
- ✓ Two relay contacts overlapping for 3 Sec
- ✓ Time range 60 Sec
- ✓ Time adjustable by Pot
- ✓ LED Indications for Main & Divider
- ✓ Auxiliary supply 230VAC / 440VAC
- ✓ Enclosure : Din Rail Mounting
- ✓ Size : 50 X 70 X 110 mm



**SSTMR**

---

---

## SPECIFICATIONS

- ✓ 4 Digit display
- ✓ 4 Key keyboard
- ✓ Min /Sec settable
- ✓ ON Delay / Interval / Cyclic settable
- ✓ LED Indications for Set, Run & Relay
- ✓ Time range 0000 to 9999 Sec or Min
- ✓ Auxiliary supply 230VAC / 440VAC
- ✓ Enclosure : ABS Plastic
- ✓ Size : 96X96X110 mm
- ✓ Panel Cutout : 90×90 mm



**DIGITAL TIMER**

---

---

## ENERTECH DEVICES

19, Parijat, Vidhyanagar Hsg. Soc. Behind Kranti Clinic, Dr. Ambedkar Rd, Sangli 416416 Maharashtra, India.

Ph:- 91(233)2530474. Suhas:- 9822794744

Website: [www.enertechdevices.com](http://www.enertechdevices.com)

Email: [suhas.tanawade@gmail.com](mailto:suhas.tanawade@gmail.com)